

High Pressure Cleaning Equipment

Cold Pressure Cleaners Also available in
a Hot Water version



- Performances ranging from 50 bar to 350 bar in 110v, 240v and 415v
- It's also available with the facility to supply it with hot water up to 85 degrees centigrade on selected models
- Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which has proven to reduce maintenance costs by 75%
- To prolong the life of the chassis it is constructed of steel which is zintec coated with a polyester finish. Also available in stainless steel
- Long life, slow revving, industrial 1400 RPM electric motor coupled to a brass headed Interpump pump
- Supplied with 9m. high pressure hose, on/off gun, lance & nozzle
- The polyethylene water tank also meets Water Bylaws regulations
- Designed and manufactured by Cleanwell to comply with CE Legislation
- 1 Year warranty subject to conditions of sale



CC COLD WATER HIGH PRESSURE CLEANERS

PERFORMANCE SPECIFICATIONS

OPERATING PRESSURE		FLOW RATE LITRES PER MINUTE	VOLTAGE	MOTOR
PSI	BAR	LITRES PER MINUTE		
1500	100	12	110V	3.0 HP
1500	100	12	240V	3.4 HP
1500	100	14	240V	3.4 HP
2200	150	14	415V	5.5 HP
2200	150	21	415V	7.5 HP
2500	175	18	415V	7.5 HP
3000	200	15	415V	7.5 HP
3625	250	15	415V	10 HP
3000	200	21	415V	10 HP
3625	250	21	415V	15 HP
3000	200	30	415V	15 HP
5076	350	15	415V	15 HP

SPECIFICATIONS

PUMP	3 PISTON PLUNGER	MAXIMUM INLET TEMP.	50°C (Cold Range)
MOTOR	INTERPUMP	AUTO TIME STOP	Adjustable
VOLTAGE CONTROLS	INDUSTRIAL SLOW REVING	WATER TANK	Standard 21 Litres
DIMENSIONS	24 VOLTS	W – 940 MM	Depth 540mm
	H – 1620 MM		

OPTIONS

ALL STAINLESS STEEL CHEMICAL SOLENOID LOCKABLE CONTROL PANEL COIN OR TOKEN OPERATION WITH TIMED CYCLES LOW PRESSURE CHEMICAL SPRUNG LOADED BOOMS	FROST PROTECTION REMOTE CONTROL KEY ISOLATOR CHEMICAL HIGH PRESSURE TWO MAN OPERATION ON/ OFF GUN WITH BRUSH	TIMED CHEMICAL OPERATION RCD RETRACTABLE HOSE REEL STAINLESS STEEL LANCE BRACKET WATER SOFTENER LARGE WATER TANKS
--	--	--

High Pressure Cleaning Equipment

Static Hot & Cold Pressure Cleaners



- Performances ranging from 50 bar to 200 bar

400 – 415 Volts. 50 Hz

ADVANTAGES OVER OIL FIRED

- No smelly diesel fumes
 - No noise from burner
 - No dirty diesel problems
 - Approx about £1 an hour cheaper to run
 - Very little servicing to be carried out
 - A more environmentally friendly machine
 - More reliable and efficient
- Stainless steel water tank which holds 300 litres. Heavily insulated to maintain a high water temperature
 - Two high efficiency immersion heaters able to produce heat up to 85°C
 - Visual digital temperature display on dashboard
 - Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which has proven to reduce maintenance costs by 75%
 - To prolong the life of the chassis it is constructed of steel which is zintec coated with a polyester finish. Also available in stainless steel
 - Low pressure chemical injection
 - Supplied with 9m. high pressure hose, on/off gun, lance & nozzle
 - Dimensions: Depth 850mm x Width 950mm x Height 1710mm
 - Designed and manufactured by Cleanwell to comply with CE Legislation
 - Environmentally friendly specification 1 Year warranty subject to conditions of sale

HS ELECTRICALLY HEATED HOT HIGH PRESSURE CLEANERS

THE OMISSION FREE HOT HIGH PRESSURE CLEANER FOR SPECIAL APPLICATIONS

The electrically heated hot water high pressure cleaner with stainless steel tank with float switch isolator for low water and digital temperature gauge. Ideal for applications whenever exhaust from oil fired pressure cleaners are undesirable or prohibited. For example food industry, abattoirs, hospitals and the chemical industry.

PERFORMANCE SPECIFICATIONS

OPERATING PRESSURE	FLOW RATE	VOLTAGE	MOTOR
OPERATING PRESSURE	170 BAR	170 BAR	3000 PSI / 200 BAR
LITRES PER MINUTE	13	13	15
TEMP. OF HEATING BOILER °C	30° - 80°	30° - 80°	30° - 80°
STAINLESS STEEL TANK CAPACITY	53 GALLONS 240 LTRS	53 GALLONS 240 LTRS	53 GALLONS 240 LTRS
CONNECTED LOAD	18 + 4 KW	24 + 4 KW	24 + 36 + 5.5 KW
VOLTS / HZ	415v / 3PH / 50	415v / 3PH / 50	415v / 3PH / 50

ALSO AVAILABLE IN 60Hz OR WITH ATEX APPROVAL ON REQUEST

High Pressure Cleaning Equipment

Static Hot & Cold Pressure Cleaners



- Performances ranging from 50 bar to 350 bar in 110v, 240v and 415v. Available as oil fired or electrically heated
- Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which has proven to reduce maintenance costs by 75%
- To prolong the life of the chassis it is constructed of zintec coated steel with a polyester finish. Also available in stainless steel

- Long life, slow revving, industrial 1400 RPM electric motor coupled to a brass headed Interpump pump
- Improved high efficiency burner which is able to produce up to 150°C through a steam valve system
- Supplied with 9m high pressure hose, on/off gun, lance & nozzle
- The polyethylene water tank also meets Water Bylaws regulations
- Designed and manufactured by Cleanwell to comply with CE Legislation
- 1 Year warranty subject to conditions of sale



HS OIL FIRED HOT HIGH PRESSURE CLEANERS

PERFORMANCE SPECIFICATIONS

OPERATING PRESSURE		FLOW RATE	VOLTAGE	MOTOR
PSI	BAR	LITRES PER MINUTE		
1500	100	12	110V	3.0 HP
1500	100	12	240V	3.4 HP
1500	100	14	240V	3.4 HP
1500	100	14	415V	5.5 HP
2200	150	14	415V	7.5 HP
2200	150	21	415V	7.5 HP
2500	175	18	415V	7.5 HP
3000	200	15	415V	7.5 HP

PUMP	3 PISTON PLUNGER INTERPUMP	MAXIMUM INLET TEMP. OUTLET	40°C
MOTOR	INDUSTRIAL SLOW REVING	TEMP RANGE	10-150°C
AUTO TIME STOP	ADJUSTABLE	WATER TANK	21 LTR
VOLTAGE CONTROLS	24 VOLTS		
DIMENSIONS	H – 1620 MM	W – 940 MM	L – 550 MM

OPTIONS

ALL STAINLESS STEEL CHEMICAL SOLENOID LOCKABLE CONTROL PANEL COIN OR TOKEN OPERATION WITH TIMED CYCLES LOW PRESSURE CHEMICAL BURNER FLAME FAILURE	FROST PROTECTION REMOTE CONTROL KEY ISOLATOR RETRACTABLE/MANUAL HOSEREEL 1000 LTR BUNDED FUEL TANK TWO MAN OPERATION	DIESEL TANK WITH FLOAT SWITCH TIMED CHEMICAL OPERATION RCD ELCB INTERNAL CHEMICAL &FUEL SUPPLY]SPRUNG LOADED BOOMS WATER SOFTENER
---	---	---